

SAE STANDARD CONNECTIONS


M12510

JIC MALE 37° CONE - SAE J516 / ISO 12151-5

MACHO JIC ASIENTO A 37° - SAE J516 / ISO 12151-5

AGJ 37° AUSSENKONUS (UNF-GEWINDE NACH SAE J516 / ISO 12151-5)

MASCHIO JIC CONO 37° - SAE J516 / ISO 12151-5



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H1
M12510-04-04	6	1/4"	-04	7/16" - 20	4,0	28,0	14,0	12	
M12510-04-05	6	1/4"	-04	1/2" - 20	5,5	29,0	14,0	14	
M12510-04-06	6	1/4"	-04	9/16" - 18	7,0	29,0	14,0	17	
M12510-05-04	8	5/16"	-05	7/16" - 20	4,0	29,0	14,0	14	
M12510-05-05	8	5/16"	-05	1/2" - 20	5,5	29,0	14,0	14	
M12510-05-06	8	5/16"	-05	9/16" - 18	7,0	29,0	14,0	17	
M12510-06-05	10	3/8"	-06	1/2" - 20	5,5	29,5	14,0	17	
M12510-06-06	10	3/8"	-06	9/16" - 18	7,0	29,6	14,0	17	
M12510-06-08	10	3/8"	-06	3/4" - 16	9,3	34,1	16,5	19	
M12510-06-10	10	3/8"	-06	7/8" - 14	12,5	38,6	19,5	24	
M12510-08-06	12	1/2"	-08	9/16" - 18	7,0	32,0	14,0	19	
M12510-08-08	12	1/2"	-08	3/4" - 16	9,3	34,4	16,5	19	
M12510-08-10	12	1/2"	-08	7/8" - 14	12,5	38,9	19,5	24	
M12510-08-12	12	1/2"	-08	1.1/16" - 12	15,0	42,9	22,0	27	
M12510-10-10	16	5/8"	-10	7/8" - 14	12,5	39,2	19,5	24	
M12510-10-12	16	5/8"	-10	1.1/16" - 12	15,0	42,7	22,0	27	
M12510-12-10	19	3/4"	-12	7/8" - 14	12,5	41,5	19,5	27	
M12510-12-12	19	3/4"	-12	1.1/16" - 12	15,0	44,0	22,0	27	
M12510-12-14	19	3/4"	-12	1.3/16" - 12	16,0	44,5	22,5	32	
M12510-12-16	19	3/4"	-12	1.5/16" - 12	19,8	47,0	23,0	34	
M12510-16-12	25	1"	-16	1.1/16" - 12	15,0	44,8	22,0	32	
M12510-16-16	25	1"	-16	1.5/16" - 12	19,8	47,8	23,0	34	
M12510-16-20	25	1"	-16	1.5/8" - 12	26,0	52,8	24,3	42	
M12510-20-20	31	1.1/4"	-20	1.5/8" - 12	26,0	53,5	24,3	42	
M12510-20-24	31	1.1/4"	-20	1.7/8" - 12	32,0	60,5	27,5	50	
M12510-24-24	38	1.1/2"	-24	1.7/8" - 12	32,0	60,5	27,5	50	
M12510-32-32	51	2"	-32	2.1/2" - 12	42,0	71,8	34,0	65	