


M22542

45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 HEMBRA JIC CODO DE 45° ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)
 DKJ 45° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)



M22543

45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 HEMBRA JIC CODO DE 45° ASIENTO A 37° - SAE J516 / ISO 12151-5 (TUERCA LIBRE)
 DKJ 45° BOGEN 37° DICHTKOPF (UND-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE		THREAD	DIMENSIONS mm						
	DN	inch		T	B	A	C	E	H _z	

	DN	inch	Size	T	B	A	C	E		H _z
M22542-03-04	5	3/16"	- 03	7/16" - 20	4,0	35,0	8,2	14,5		17
M22542-04-04	6	1/4"	- 04	7/16" - 20	4,0	35,5	8,2	14,5		17
M22542-04-05	6	1/4"	- 04	1/2" - 20	4,0	35,7	9,2	14,5		17
M22543-04-06	6	1/4"	- 04	9/16" - 18	4,0	35,5	9,8	14,0		19
M22542-05-05	8	5/16"	- 05	1/2" - 20	5,5	37,5	9,2	14,5		17
M22542-05-06	8	5/16"	- 05	9/16" - 18	7,0	38,0	9,2	14,5		19
M22542-06-06	10	3/8"	- 06	9/16" - 18	7,0	42,0	9,2	16,5		19
M22543-06-08	10	3/8"	- 06	3/4" - 16	7,0	41,0	10,7	14,0		22
M22543-06-10	10	3/8"	- 06	7/8" - 14	9,3	42,5	12,4	15,5		27
M22542-08-08	12	1/2"	- 08	3/4" - 16	9,3	52,0	10,2	20,0		22
M22543-08-10	12	1/2"	- 08	7/8" - 14	9,3	49,5	12,4	17,0		27
M22543-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	50,0	13,8	17,0		32
M22542-10-10	16	5/8"	- 10	7/8" - 14	12,5	62,0	12,3	25,5		27
M22543-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	60,0	13,8	24,0		32
M22542-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	70,0	14,2	27,5		32
M22542-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	69,0	14,8	27,5		36
M22542-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	70,0	15,2	27,5		38
M22542-16-12	25	1"	- 16	1.1/16" - 12	15,0	72,5	14,2	27,5		32
M22542-16-16	25	1"	- 16	1.5/16" - 12	19,8	86,0	15,2	32,0		38
M22542-16-20	25	1"	- 16	1.5/8" - 12	26,0	90,0	16,2	36,0		50
M22542-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	103,5	16,2	41,5		50
M22542-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	106,5	18,8	44,5		60
M22542-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	119,0	18,8	46,5		60
M22542-32-32	51	2"	- 32	2.1/2" - 12	44,0	163,0	24,0	68,0		75