

SAE STANDARD CONNECTIONS

M22712

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)


HEMBRA JIC ASIENTO A 37° DOBLE TUERCA SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)

DKJ 37° DK MIT KONTERSECHSKANT

(UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO

SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M22712-03-04	5	3/16"	- 03	7/16" - 20	4,0	20,5	8,2		12	17
M22712-04-04	6	1/4"	- 04	7/16" - 20	4,0	21,0	8,2		12	17
M22712-04-05	6	1/4"	- 04	1/2" - 20	4,0	21,5	9,2		12	17
M22712-04-06	6	1/4"	- 04	9/16" - 18	7,0	24,1	9,2		14	19
M22712-05-05	8	5/16"	- 05	1/2" - 20	5,5	21,5	9,2		14	17
M22712-05-06	8	5/16"	- 05	9/16" - 18	7,0	24,1	9,2		14	19
M22712-05-08	8	5/16"	- 05	3/4" - 16	9,3	26,0	10,6		19	22
M22712-06-04	10	3/8"	- 06	7/16" - 20	4,0	24,5	8,2		17	17
M22712-06-05	10	3/8"	- 06	1/2" - 20	5,5	25,0	9,2		17	17
M22712-06-06	10	3/8"	- 06	9/16" - 18	7,0	24,6	9,2		17	19
M22712-06-08	10	3/8"	- 06	3/4" - 16	9,3	27,1	10,2		19	22
M22712-06-10	10	3/8"	- 06	7/8" - 14	12,5	28,0	12,3		22	27
M22712-08-06	12	1/2"	- 08	9/16" - 18	7,0	24,7	9,2		19	19
M22712-08-08	12	1/2"	- 08	3/4" - 16	9,3	27,4	10,2		19	22
M22712-08-10	12	1/2"	- 08	7/8" - 14	12,5	28,4	12,3		22	27
M22712-08-12	12	1/2"	- 08	1.1/16" - 12	14,0	30,0	14,2		27	32
M22712-10-08	16	5/8"	- 10	3/4" - 16	9,3	28,5	10,2		22	27
M22712-10-10	16	5/8"	- 10	7/8" - 14	12,5	29,0	12,3		22	27
M22712-10-12	16	5/8"	- 10	1.1/16" - 12	15,0	29,5	14,2		27	32
M22712-12-08	19	3/4"	12	3/4" - 16	9,3	30,0	10,2		27	22
M22712-12-10	19	3/4"	- 12	7/8" - 14	12,5	30,0	12,3		27	27
M22712-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	31,5	14,2		27	32
M22712-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	33,0	14,8		30	36
M22712-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	32,5	15,2		32	38
M22712-16-12	25	1"	- 16	1.1/16" - 12	12,5	33,8	14,2		32	32
M22712-16-16	25	1"	- 16	1.5/16" - 12	19,8	34,3	15,2		32	38
M22712-16-20	25	1"	- 16	1.5/8" - 12	26,0	42,8	16,2		41	50
M22712-20-16	31	1.1/4"	- 20	1.5/16" - 12	19,8	36,0	15,2		38	38
M22712-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	43,5	16,2		41	50
M22712-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	51,0	18,8		50	60
M22712-32-32	51	2"	- 32	2.1/2" - 12	42,0	55,5	24,0		65	75