


BS STANDARD CONNECTIONS


M20512

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 HEMBRA BSP ASIEN TO A 60° - BS5200 / ISO 12151-6 (TUERCA CON SEGURO)
 DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)



M20513

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 HEMBRA BSP ASIEN TO A 60° - BS5200 / ISO 12151-6 (TUERCA LIBRE)
 DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)
 FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₂
M20512-03-02	5	3/16"	- 03	1/8" - 28	3,1	14,8	4,4		14
M20513-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	5,4		19
M20512-04-02	6	1/4"	- 04	1/8" - 28	3,1	15,5	4,4		14
M20513-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,0	5,4		19
M20513-04-06	6	1/4"	- 04	3/8" - 19	7,0	19,1	6,0		22
M20512-05-04	8	5/16"	- 05	1/4" - 19	4,1	17,5	4,2		19
M20513-05-06	8	5/16"	- 05	3/8" - 19	7,0	19,1	6,0		22
M20513-05-08	8	5/16"	- 05	1/2" - 14	9,3	20,5	6,5		27
M20512-06-04	10	3/8"	- 06	1/4" - 19	4,1	18,1	4,2		19
M20513-06-06	10	3/8"	- 06	3/8" - 19	7,0	19,6	6,0		22
M20513-06-08	10	3/8"	- 06	1/2" - 14	9,3	20,0	6,5		27
M20512-08-06	12	1/2"	- 08	3/8" - 19	7,1	20,9	6,0		22
M20513-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5		27
M20512-08-10	12	1/2"	- 08	5/8" - 14	12,1	21,9	10,2		28
M20512-08-12	12	1/2"	- 08	3/4" - 14	15,0	23,4	9,0		32
M20512-10-08	16	5/8"	- 10	1/2" - 14	9,8	24,0	6,5		27
M20512-10-10	16	5/8"	- 10	5/8" - 14	12,5	21,7	10,2		28
M20512-10-12	16	5/8"	- 10	3/4" - 14	15,0	23,2	9,0		32
M20512-12-08	19	3/4"	- 12	1/2" - 14	9,8	25,0	6,5		27
M20512-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0		32
M20512-12-16	19	3/4"	- 12	1" - 11	19,8	26,0	10,5		38
M20512-16-12	25	1"	- 16	3/4" - 14	15,0	25,5	9,0		32
M20512-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,5		38