



### M20592

90° BSP FEMALE SWEEP ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)  
 HEMBRA BSP CODO DE 90° ASIENTO A 60° - BS5200 / ISO 12151-6 (TUERCA CON SEGURO)  
 DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)  
 FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)

### M20593

90° BSP FEMALE SWEEP ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)  
 HEMBRA BSP CODO DE 90° ASIENTO A 60° - BS5200 / ISO 12151-6 (TUERCA LIBRE)  
 DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)  
 FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE		THREAD	DIMENSIONS mm						
------------	-----------	--	--------	------------------	--	--	--	--	--	--

	DN	inch	Size	T	B	A	C	E		H <sub>2</sub>
M20592-03-02	5	3/16"	- 03	1/8" - 28	3,1	21,5	4,4	26,0		14
M20593-03-04	5	3/16"	- 03	1/4" - 19	4,0	29,0	5,4	29,0		19
M20592-04-02	6	1/4"	- 04	1/8" - 28	3,1	28,5	4,4	27,0		14
M20593-04-04	6	1/4"	- 04	1/4" - 19	4,0	29,5	5,4	29,0		19
M20593-04-06	6	1/4"	- 04	3/8" - 19	7,0	29,5	6,0	31,0		22
M20592-05-04	8	5/16"	- 05	1/4" - 19	4,1	26,5	5,4	29,5		19
M20593-05-06	8	5/16"	- 05	3/8" - 19	7,0	32,0	6,0	27,5		22
M20593-05-08	8	5/16"	- 05	1/2" - 14	9,3	36,5	6,5	32,0		27
M20592-06-04	10	3/8"	- 06	1/4" - 19	4,0	27,0	4,2	29,5		19
M20593-06-06	10	3/8"	- 06	3/8" - 19	7,0	36,5	6,0	31,5		22
M20593-06-08	10	3/8"	- 06	1/2" - 14	9,3	36,5	6,5	32,0		27
M20592-08-06	12	1/2"	- 08	3/8" - 19	7,0	45,0	6,0	41,0		22
M20593-08-08	12	1/2"	- 08	1/2" - 14	9,3	45,0	6,5	36,5		27
M20592-08-10	12	1/2"	- 08	5/8" - 14	12,1	44,0	10,2	44,0		28
M20592-08-12	12	1/2"	- 08	3/4" - 14	15,0	44,0	9,0	45,5		32
M20592-10-08	16	5/8"	- 10	1/2" - 14	9,3	53,5	6,5	54,5		27
M20592-10-10	16	5/8"	- 10	5/8" - 14	12,5	53,5	10,2	53,5		28
M20592-10-12	16	5/8"	- 10	3/4" - 14	15,0	53,5	9,0	55,0		32
M20592-12-08	19	3/4"	- 12	1/2" - 14	9,3	45,5	6,5	44,0		27
M20592-12-12	19	3/4"	- 12	3/4" - 14	15,5	61,5	9,0	59,5		32
M20592-12-16	19	3/4"	- 12	1" - 11	19,8	61,5	10,5	62,0		38
M20592-16-12	25	1"	- 16	3/4" - 14	15,0	64,5	9,0	59,5		32
M20592-16-16	25	1"	- 16	1" - 11	19,8	79,5	10,5	76,0		38