



M20812



BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 HEMBRA BSP CON O-RING ASIENTO A 60° - BS5200 / ISO 12151-6 (TUERCA CON SEGURO)
 DKOR 60° KONUS MIT O-RING -
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 GESTIFTETE MUTTER)
 FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)

M20813



BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 HEMBRA BSP CON O-RING ASIENTO A 60° - BS5200 / ISO 12151-6 (TUERCA LIBRE)
 DKOR 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGTE MUTTER)
 FEMMINA GAS CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₂	

PART. REF.	DN	inch	Size	T	B	A	C	H ₂
M20813-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	4,9	19
M20813-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,5	4,9	19
M20812-06-04	10	3/8"	- 06	1/4" - 19	4,0	18,1	4,9	19
M20813-06-06	10	3/8"	- 06	3/8" - 19	7,0	20,4	6,1	22
M20813-06-08	10	3/8"	- 06	1/2" - 14	9,3	21,0	6,5	27
M20813-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5	27
M20812-10-10	16	5/8"	- 10	5/8" - 14	12,5	22,1	9,7	28
M20812-12-12	19	3/4"	- 12	3/4" - 14	15,0	25,0	8,5	32
M20812-16-12	25	1"	- 16	3/4" - 14	15,0	26,0	8,5	32
M20812-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,6	38
M20812-16-20	25	1"	- 16	1.1/4" - 11	26,1	30,8	10,5	50
M20812-20-16	31	1.1/4"	- 20	1" - 11	19,8	29,0	10,5	38
M20812-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	31,5	10,5	50
M20812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,1	29,5	12,5	60
M20812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	31,5	10,5	50
M20812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	30,5	12,5	60
M20812-24-32	38	1.1/2"	- 24	2" - 11	42,0	30,0	16,1	70
M20812-32-32	51	2"	- 32	2" - 11	42,0	31,9	16,1	70