


MULTIFIT TYPE



SAE STANDARD CONNECTIONS

M22582F


90° JIC FEMALE COMPACT ELBOW 37° CONE SEAT
 SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 HEMBRA JIC CODO COMPACTO DE 90° ASIENTO A 37°
 SAE J516 / ISO 12151-5 (TUERCA CON SEGURO)
 DKJ 90° KOMPAKT BOGEN 37° DICHTKOPF
 (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC 90° TIPO COMPATTO CONO 37°
 SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H ₁
M22582-04-04F	6	1/4"	- 04	7/16" - 20	4,0	20,0	8,2	20,5	14	17
M22582-04-06F	6	1/4"	- 04	9/16" - 18	7,0	20,0	9,2	21,5	14	19
M22582-06-06F	10	3/8"	- 06	9/16" - 18	7,0	23,1	9,2	24,0	19	19
M22582-06-08F	10	3/8"	- 06	3/4" - 16	9,3	26,6	10,2	28,0	22	22
M22582-08-08F	12	1/2"	- 08	3/4" - 16	9,3	24,9	10,2	28,0	22	22
M22582-08-10F	12	1/2"	- 08	7/8" - 14	12,5	24,9	12,3	29,0	22	27
M22582-12-12F	19	3/4"	- 12	1.1/16" - 12	15,0	37,5	14,2	33,0	27	32
M22582-16-16F	25	1"	- 16	1.5/16" - 12	20,0	51,8	15,2	40,0	36	38

M12410

ORFS MALE - SAE J516 / ISO 12151-1
 MACHO ORFS - SAE J516 / ISO 12151-1
 ORFS AUSSENGEWINDE NACH SAE J516 / ISO 12151-1
 MASCHIO ORFS - SAE J516 / ISO 12151-1



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	H ₁	H ₂
M12410-04-04	6	1/4"	- 04	9/16" - 18	4,0	24,0	9,8		16	
M12410-04-06	6	1/4"	- 04	11/16" - 16	6,7	26,6	11,2		19	
M12410-05-06	8	5/16"	- 05	11/16" - 16	6,7	27,0	11,2		19	
M12410-06-06	10	3/8"	- 06	11/16" - 16	6,7	27,6	11,2		19	
M12410-06-08	10	3/8"	- 06	13/16" - 16	9,3	30,0	12,8		22	
M12410-08-08	12	1/2"	- 08	13/16" - 16	9,3	30,6	12,8		22	
M12410-08-10	12	1/2"	- 08	1" - 14	12,5	35,0	15,5		27	
M12410-08-12	12	1/2"	- 08	1.3/16" - 12	15,0	37,5	17,0		32	
M12410-10-08	16	5/8"	- 10	13/16" - 16	9,3	30,5	12,8		22	
M12410-10-10	16	5/8"	- 10	1" - 14	12,5	34,7	15,5		27	
M12410-10-12	16	5/8"	- 10	1.3/16" - 12	15,0	37,5	17,0		32	
M12410-12-12	19	3/4"	- 12	1.3/16" - 12	15,0	39,0	17,0		32	
M12410-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	40,5	17,5		38	
M12410-16-16	25	1"	- 16	1.7/16" - 12	19,8	41,8	17,5		38	
M12410-16-20	25	1"	- 16	1.11/16" - 12	26,0	44,0	17,5		46	
M12410-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	46,3	17,5		46	
M12410-24-24	38	1.1/2"	- 24	2" - 12	32,0	48,6	17,5		55	