

SAE STANDARD CONNECTIONS


M24493*

90° ORFS FEMALE LONG DROP ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT)

HEMBRA ORFS CODO DE 90° LARGO - SAE J516 / ISO 12151-1 (TUERCA LIBRE)

DK 90° BOGEN ORFS LANGE SCHENKEL (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER)

FEMMINA ORFS A 90° CURVA LUNGA - SAE J516 / ISO 12151-1 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H ₂
M24493-04-04	6	1/4"	- 04	9/16" - 18	4,4	24,5	8,2	45,5		17
M24493-04-06	6	1/4"	- 04	11/16" - 16	7,0	24,5	9,5	53,5		22
M24493-06-06	10	3/8"	- 06	11/16" - 16	7,0	31,5	9,5	53,5		22
M24493-06-08	10	3/8"	- 06	13/16" - 16	6,7	32,0	11,0	53,5		24
M24493-08-08	12	1/2"	- 08	13/16" - 16	10,0	37,0	11,0	63,5		24
M24493-08-10	12	1/2"	- 08	1" - 14	9,6	37,0	13,5	64,0		30
M24493-10-10	16	1/2"	- 10	1" - 14	9,6	41,0	13,5	69,0		30
M24493-10-12	16	5/8"	- 10	1.3/16" - 12	12,7	41,0	14,5	73,0		36
M24493-12-12	19	5/8"	- 12	1.3/16" - 12	15,5	45,5	14,5	96,0		36
M24493-16-16	25	1"	- 16	1.7/16" - 12	20,6	58,5	14,8	113,5		41

* Brazed solution / Con soldadura / Lötausführung / Con saldatura